

AMENDMENTS TO THE CLAIMS:

Please cancel claims 62-66, 68-70, and 99-100, and add new claims 115-121 as follows:

62-66. (Cancelled).

68-70. (Cancelled).

99-100. (Cancelled).

115. (New) The machine according to claim 1, wherein:

only one of the rear supports is configured to move inward of said frame and is configured to be rotatable about the rear vertical axis only when positioned inward of said frame.

116. (New) The steerable machine for breaking up ground as claimed in claim

9, wherein:

only one of said rear supports is pivotable about the rear vertical axis;

the pivotable rear support is pivotable between an extended position and a retracted position; and

the pivotable rear support is steerable only when in said retracted position.

117. (New) A machine according to claim 48, wherein only the first rear support is pivotable about a vertical axis and the first rear support is selectively steerable at the same time with the front supports only when the first rear support is in a retracted position.

118. (New) A machine according to claim 71, wherein:
only one of the rear supports is pivotable about the first rear vertical axis; and
the steering system is configured to rotate the pivotable one of the rear supports
about the second rear vertical axis only when the pivotable one of the rear supports is
moved inward of said frame.

119. (New) A machine according to claim 77, wherein:
only one of said rear supports is pivotable about the rear vertical axis;
said pivotable rear support is pivotable between an extended position and a
retracted position; and
said pivotable rear support is steerable only when in said retracted position.

120. (New) A machine according to claim 103, wherein only the first rear
support is pivotable about a vertical axis and the first rear support is selectively
steerable at the same time with the front supports only when the first rear support is in a
retracted position.

121. (New) A machine according to claim 107, wherein:
only one of said rear supports is pivotable about the rear vertical axis;
said pivotable rear support is pivotable between an extended position and a
retracted position; and
said pivotable rear support is steerable only when in said retracted position.